



A Safety Data Sheet is not legally required for this product under the OSHA Hazard Communication Standard (29 CFR 1910.1200). The following information is provided as a courtesy service to our customers.

SECTION 1: IDENTIFICATION

Product identifier

Trade name:

POLYETHYLENE FOAM PRODUCTS, natural plus colors*, including Astro-Barrier™, Astro-Foam®, Astro-Foam® Renew™, Furniture Guard® Roll / Sheet products, PolyPlank® LAM, PolyPlank® MDL, PolyPlank® EXT, PolyPlank® SFT, PolyPlank® RenewTM, Proflex® Profiles, Corner Keeper™, Edge Foam®.

* This MSDS pertains only to natural and/or pigmented products formulated without anti-static and/or fire retardant additives, adhesive components, or other specialty additives.

Synonym(s):

None known

Preparation/Revision date:

6 March 2015

Relevant identified uses of the substance or mixture and uses advised against

Identified uses:

Protective packaging - Flexible polyethylene foam

Uses advised against:

None known

Details of the supplier of the safety data sheet

Manufacturer / Supplier

Company name:

Pregis Innovative Packaging, Inc.

Address:

1650 Lake Cook Road, Suite 400

Deerfield, IL 60015

Customer service:

877-692-6163

Emergency telephone number

For product and additional safety information:

e-Mail: gallen@pregis.com

24-Hour Emergency Contact: Chemtrec: (800) 424-9300

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Not regulated per OSHA Hazard Communication Standard 29 CFR

1910.1200.



This product conforms to the U.S. OSHA Hazard Communication Standard's definition of an "Article," i.e., "...a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees.

Label elements

Contains:

None

Hazard pictogram:

None

Signal word:

None

Hazard statement:

None

Precautionary statements:

- Prevention:

None

- Response:

None

- Storage:

None

- Disposal:

None

Supplemental label information:

None

Other hazards

None

Hazard summary

Physical hazards:

Not classified for physical hazards.

Health hazards:

Not classified for health hazards.

Environmental hazards:

Not classified for hazards to the environment.

Main symptoms:

Eye contact may clause slight irritation. In rare cases, sensitive individuals may experience irritation or reddening of skin. Inhalation of processing fumes or dusts

may cause upper respiratory irritation.



SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

This product conforms to the U.S. OSHA Hazard Communication Standard's definition of an "Article," i.e., "...a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees." The following information is provided as a courtesy.

Chemical Name	Percent	CAS No.	Notes	
Polyethylene resin	≥ 84			
Ethene/Butene Copolymer		25087-34-7		
Tris-nonylphenyl phosphite		26523-78-4		
Polyethylene Homopolymer		9002-88-4		
Crystalline silica		68855-54-9		
Hydrocarbon Foaming Agents	≤5			
Isobutane		75-28-5		
n-butane		106-97-8		
Talc (Magnesium silicate)	≤ 4	14807-96-6		
Foam Processing Aid, Monodiglycerides	≤2	67701-33-1		
Organic and/or inorganic colorants	≤5	Various		

Composition comments: Organic and/or inorganic colorants, which may include carbon black pigment which is thoroughly bound to the polymer matrix.

SECTION 4: FIRST AID MEASURES

General Information	Show this Safety Data Sheet to the medical professional in attendance		
	Adverse health effects are not anticipated with use of this product as		
	intended. If symptoms occur, follow first aid measures as appropriate.		

	interface. If symptoms occur, follow mat aid measures as appropriate.
Description of first aid measure	es control of the con
Inhalation:	If symptoms are experienced, move victim to fresh air, if symptoms persist,
	obtain medical attention.
Skin contact:	Wash contaminated skin with mild soap and water. Get medical attention if
	irritation develops or persists.
Eye contact:	Rinse immediately with plenty of water, including under the eyelids. Get
	medical attention if irritation develops or symptoms persist.



SECTION 4: FIRST AID MEASURES (CONT'D)

Ingestion:

If gastric irritation or discomfort persists seek medical advice.

Notes to Physician:

None specified

Most important symptoms

and effects, both acute and delayed

Eye contact may clause slight irritation. In rare cases, individuals may experience irritation or reddening of skin. Inhalation of processing fumes or dusts may cause upper respiratory irritation.

Indication of any immediate medical attention and special treatment needed

None known

SECTION 5: FIRE FIGHTING MEASURES

General fire hazards

Flammability not established for product as a whole. Polyethylene is combustible. Pregis's polyethylene foam also contains some residual flammable blowing agent, which might accumulate in confined spaces to produce concentrations in the explosive range. Processes such as grinding could produce fine dust and flammable vapors. Both could be potential explosion hazards.

Extinguishing Media

Suitable extinguishing media:

Water, Foam, Dry Chemical, Carbon Dioxide. Use extinguishing media

appropriate for surrounding material.

Unsuitable extinguishing media:

None known

Special hazards arising from the

substance or mixture

Temperatures above 480°F could cause product degradation potentially producing toxic vapors including carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and/or

alcohols.

Advice for firefighters

Special protective equipment for firefighters:

Firefighters should use self-contained breathing apparatus and wear full protective equipment. Personnel / bystanders should be kept upwind of

fire.

Special firefighting procedures:

Not applicable

Special remarks on fire hazards:

None

Preparation Date: 6 March 2015 Page 4 of 12



SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Protective clothing is not required under normal conditions of intended use, however, the use of gloves and safety glasses is consistent with good manufacturing and hygienic practice.

Methods and materials for containing and cleaning up

No special measures necessary beyond general housekeeping. Pick up and retaining material for recycling or disposal.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Further processing of polyethylene foam products with any fabrication processes such as slitting, grinding, skiving, sawing, routing, or die cutting that cuts cells can release residual flammable blowing agent. A flammable concentration could accumulate if air is not properly circulated. All sources of ignition should be prevented in areas where foam is fabricated. Humidifiers or ionized air blowers can be used to reduce the possibility of static spark. Grinding equipment and any bins or hoppers should be purged with a positive air flow to dissipate any build-up of blowing agent gases. Monitoring systems should be in place to insure that a concentration of blowing agent does not accumulate during shutdowns or malfunctions. For hot wire cutting or thermal welding air flow should be provided to adequately disperse potential blowing agent build up. Control any vapor or dust emissions that may be generated by further processing of product.

Conditions for safe storage, including any incompatibilities

Always store polyethylene foam products in well-ventilated areas. Always keep foam products away from excessive heat and any sources of ignition such as sparks or flame. Never store foam in confined areas or sealed-off compartments. Foam scrap or fabricated parts for disposal should be stored and shipped in ventilated containers. When opening doors and unloading foam shipments, extinguish all possible sources of ignition such as matches, cigarettes, sparks, and lighters. Allow air circulation into the trailer for ten minutes after opening trailer doors before unloading foam.



SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

United States.	Occupational	Exposure Limits
----------------	--------------	-----------------

Component	CAS No.	Туре	Value	Form
Nuisance dust	N/A	ACGIH TWA	10 mg/m ³	Total dust
Nuisance dust	N/A	ACGIH TWA	3 mg/ m ³	Respirable dust
Nuisance dust	N/A	OSHA PEL	15 mg/ m ³	Total dust
Nuisance dust	N/A	OSHA PEL	5 mg/ m ³	Respirable dust
Crystalline Silica	68855-54-9	OSHA TWA	0.05 mg/ m^3	-
Crystalline Silica	68855-54-9	ACGIH TWA	0.05 mg/ m^3	-
isobutane	75-28-5	NIOSH TWA	800 ppm	
n-Butane	106-97-8	ACGIH TWA	800 ppm	-
n-Butane	106-97-8	NIOSH TWA	800 ppm	•
Hydrous magnesium silicate	14807-96-6	NIOSH TWA	2 mg/ m ³	-
Hydrous magnesium silicate	14807-96-6	ACGIH TWA	2 mg/ m^3	•
Hydrous magnesium silicate	14807-96-6	OSHA PEL	20 mppcf	-
Hydrous magnesium silicate	14807-96-6	NIOSH IDLH	1000 mg/m^3	-

Appropriate engineering controls

Local ventilation should be provided if product is further processed producing dust or fumes. General ventilation may also be used, but local ventilation is usually preferable.

Individual Protective Measures

General Information: The following general hygiene considerations are recognized as common,

good industrial hygiene practices. Wash hands after use and before

eating, avoid breathing dust, and wear safety glasses.

Wear safety glasses. While safety glasses are not required under normal Eye/face protection:

> conditions of intended use, wearing safety glasses is consistent with good manufacturing / hygienic practice and recommended if product is

further processed.

Wear protective gloves. While protective gloves are not required under Skin protection:

normal conditions of intended use, wearing protective gloves is

consistent with good manufacturing / hygienic practice.

If product is being further processed producing dust or fumes and Respiratory protection:

> adequate ventilation should be provided. In case of inadequate ventilation or risk of inhalation of dust or fumes, wear a suitable air

purifying respirator with particle filter or dust mask.

Thermal hazards: None known

Page 6 of 12 Preparation Date: 6 March 2015



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Form	Solid plastic foam	Explosive properties	Not applicable
Color	Various colors	Explosive limit	Not applicable
Odor	Odorless	Vapor pressure	Not applicable
Odor threshold	Not applicable	Vapor density	Not applicable
pH	Not applicable	Evaporation rate	Not applicable
Melting/freezing point	220°F	Relative density	0.87-1.05 (polyethylene resin)
Boiling point, initial boiling point and boiling range	Not applicable	Partition coefficient (n-octanol/water)	Not applicable
Flash point	Not applicable	Solubility (water)	Insoluble in water
Auto-ignition temperature	343°C (polyethylene resin)	Decomposition temperature	> 480°F
Flammability (solid, gas)	Will burn but does not ignite readily	Bulk density	Not applicable
Flammability limit-lower%	Not applicable	Viscosity	Not applicable
Flammability limit-upper%	Not applicable	VOC (weight %)	Not applicable
Oxidizing properties	Not applicable	Percent volatile	Not applicable

SECTION 10: STABILITY AND REACTIVITY

ReactivityThe product is stable and non-reactive under normal conditions of use,

storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization will not occur.

Conditions to avoid Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

Incompatible materials Strong oxidizers

Hazardous decompositions products

Temperatures above 480°F could cause product degradation potentially

producing toxic vapors including carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and/or

alcohols.



SECTION 11: TOXICOLOGICAL INFORMATION

General	informatio	n on likely rout	oc of avanctira
General	intormatio.	n on likely rout	es or exposure

Ingestion: No adverse effects known to be associated with ingestion of small

amounts of this inert material. Ingestion of large quantities may result

in gastrointestinal discomfort or distress.

Inhalation: Inhalation of fumes from heated plastic may cause irritation of

respiratory tract, chest discomfort, and/or dizziness. Inhalation of dust may cause respiratory irritation. Polyethylene dust from grinding and pulverizing operations is considered nuisance dust.

Skin contact: In rare cases, contact with sensitive individuals' skin may result in irritation

or reddening of skin.

Eye contact: May cause slight irritation.

Symptoms: Eye contact may clause slight irritation. In rare cases, sensitive

individuals may experience irritation or reddening of skin. Inhalation of

processing fumes or dusts may cause upper respiratory irritation.

11.1 Information on toxicological effects

Acute Toxicity: No data were identified for this product as a whole. Polyethylene resin

(main ingredient) not considered to be toxic to humans or animals. Rats inhaling polyethylene dust developed mild inflammatory changes in the lungs. Prolonged inhalation of thermal degradation products from polyethylene caused neurological effects in rats. Animal studies showed no adverse health effects on the digestive system when fed up to 20%

polyethylene.

Serious Eye Damage/Irritation: No data were identified for this product as a whole. At elevated

temperatures, such as produced by hot cutting, fumes may cause eye

irritation.

Skin corrosion/Irritation: No data were identified for this product as a whole. No skin effects are

expected from polymer contact.

Respiratory/Skin Sensitization: No data were identified for this product as a whole. Inhalation at

ambient temperatures unlikely except for dust from grinding. At elevated temperatures, such as produced by hot cutting, fumes may

cause respiratory irritation.

Germ Cell Mutagenicity: No data were identified for this product.

Preparation Date: 6 March 2015 Page 8 of 12



Section 11: Toxicological Information (cont'd)

Carcinogenicity: Crystalline silica (< 0.1%): IARC-classified 1 (Proven for human); NTP-

Classified 2 (Reasonably anticipated) target organ is the lung. Release of these materials may occur in small quantities during processing of the

product, but is not expected to present a hazard.

Reproductive Toxicity:

Developmental Effects:

No data were identified for this product.

No data were identified for this product.

No data were identified for this product.

STOT – Repeated Exposure: No data were identified for this product as a whole. Subchronic (50 to 90

day) feeding studies conducted on rats, dogs, and swine showed no effects from dietary levels of 1 to 20% powdered and shredded

polyethylene.

Aspiration Hazard: Not relevant based on physical form of the product.

Conclusion/Summary Eye contact may clause slight irritation. In rare cases, sensitive

individuals may experience irritation or reddening of skin. Inhalation of

processing fumes or dusts may cause upper respiratory irritation.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity No data were identified for this product as a whole. Polyethylene resin

(main ingredient) ecotoxicity is expected to be low.

Persistence and degradability No data were identified for this product.

Bioaccumulative potentialNo data were identified for this product as a whole. Polyethylene resin

(main ingredient) is not expected to bioaccumulate.

Mobility No data available

Results of PBT and vPvB assessment Not a PBT or vPvB material

Other adverse effects None known

Conclusion/SummaryThe material should pose no significant hazard to the environment.

Preparation Date: 6 March 2015 Page 9 of 12



SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Residual waste: Dispose as normal, non-hazardous, solid waste, in accordance with

applicable Federal, State and Local regulations.

Contaminated packaging: Dispose as normal, non-hazardous, solid waste, in accordance with

applicable Federal, State and Local regulations.

Disposal methods/information: This material is NOT classified as a Hazardous Material by RCRA.

SECTION 14: TRANSPORT INFORMATION

UN Number Not applicable, not regulated as hazardous for transport.

UN proper shipping nameNot applicable, not regulated as hazardous for transport.

Transport hazard class(es)

Not applicable, not regulated as hazardous for transport.

Packing group Not applicable, not regulated as hazardous for transport.

Environmental hazards Not applicable, not regulated as hazardous for transport.

Special precautions for user Not applicable, not regulated as hazardous for transport.

Transport in bulk according to Annex II MARPOL73/78 and the IBC

Code Not applicable, not regulated as hazardous for transport.

The transport regulation may vary based on the country of use. Check for the appropriate regulations in the country of transport or usage of this product.

Preparation Date: 6 March 2015 Page 10 of 12



SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal Regulations

29 CFR 1910.1200 Hazard Communication Standard (HCS):

TSCA (TSCA 12b):

Nonylphenol (a trivial component

of polyethylene)

Not regulated

None

CERCLA 102A / 103: SARA III, Sec. 302:

None

CALIFORNIA PROPOSITION 65:

No label required.

Other Regulations

All shipping mailer packaging and packaging components, manufactured in the United States by Pregis Innovative Packaging, Inc., comply with the several United States' enacted provisions of the Coalition of Northeast Governors ("CONEG") legislative model for the reduction of toxics in packaging and the California Toxics in Packaging Prevention Act. Pregis Innovative Packaging, Inc.'s manufacturing practices prohibit the intentional introduction of cadmium(Cd), hexavalent chromium(Cr +6), lead (Pb), or mercury (Hg) into its products' formulations. Further, the cumulative total of all such metals' incidental concentrations does not exceed 100 parts per million (ppm).

SECTION 16: OTHER INFORMATION

List of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CERCLA Comprehensive Environmental Response, Compensation, and Liability

Act

CFR Code of Federal Regulations

IARC International Agency for Research on Cancer

IBC International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

MARPOL International Convention for the Prevention of Pollution from Ships

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration (United States)

PEL Permissible Exposure Limit



RCRA

SAFETY DATA SHEET

SECTION 16: OTHER INFORMATION (CONT'D)

PBT Persistent, Bioaccumulative and Toxic

Resource Conservation and Recovery Act

SARA Superfund Amendments and Reauthorization Act

SDS Safety Data Sheet

TSCA Toxic Substances Control Act

TWA Time Weighted Average

vPvB Very Persistent and Very Bioaccumulative

SDS Revisions SDS prepared on 6 March 2015

Disclaimer Information provided by sources external to our company and set forth

herein is offered in good faith as accurate, but without guarantee. Safety precautions contained herein cannot anticipate all individual and unique situations. Conditions of use and suitability of the product for particular uses are beyond our control. All risks of use of the product are, therefore, assumed by the user and we expressly disclaim all warranties of every kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product. Nothing herein is intended as recommendation for uses which infringe valid patents or as extension of license under valid patents. Appropriate warnings and safe handling procedures should be provided to users.

Preparation Date: 6 March 2015 Page 12 of 12